LOCATION 10184

PCB CONTAMINATION STUDY

Submitted to:

THOMPSON FACILITY St. Louis, Missouri

Submitted by:

ENVIRONMENTAL SCIENCE & ENGINEERING, INC. St. Louis, Missouri

ESE No. 590-1157-0100

October 1990



A CILCORP Company

Environmental Science & Engineering, Inc.

200072081

S00072981 SUPERFUND RECORDS

TABLE OF CONTENTS

Section		Page
1.0	INTRODUCTION	1
2.0	SITE HISTORY	1
	2.1 INITIAL EVALUATION 2.2 CONCRETE REMOVAL	1
	2.3 INSPECTION-MDNR	1
	2.4 REMEDIATION VERIFICATION STUDY	
	2.5 DUST AND SOIL REMOVAL	3 3 3 3
	2.6 EPA STUDY	3
	2.7 WASTE ADVISORY, INC. STUDY	3
3.0	ESE STUDY	4
	3.1 SURFACE WIPES	4
	3.2 FLOOR DRAIN SAMPLE	5
	3.3 DUST SAMPLE	. 6
	3.4 CONCLUSIONS	6
	APPENDICES	
	A Environmental Operations, Inc.'s Initial Study	
	B <u>USEPA Letter Concerning MDNR Inspection</u>	
	C Laboratory Data from the Environmental	
	Operations, Inc. Remediation Verification Study D Laboratory Data from EPA Sampling	
	E Waste Advisory, Inc. Report	
	F Laboratory Report from the ESE Study	
	G Site Photographs from the ESE Study	
	O DITC I HOUSE ADID HOLD WILL HOLD DIEGY	

1.0 INTRODUCTION

This report presents the results obtained by Environmental Science & Engineering, Inc. (ESE) during its investigation of polychlorinated biphenyls (PCBs) contamination at the former Carter Carburetor facility, 2800 North Spring, St. Louis, Missouri. The objective of this investigation was to determine the extent of PCB contamination, review the results of previous studies, and evaluate the site in respect to remediation options and costs.

2.0 SITE HISTORY

The environmental sampling and remediation work performed in the <u>transformer-circuit</u> breaker area to date are summarized in Table 2-1 and described in the following sections.

2.1 INITIAL EVALUATION

An initial evaluation of the site was performed by Environmental Operations, Inc. (EO) in January 1989. According to the EO report (Appendix A) six high level transformers and 16 oil-cooled circuit breakers were located in the study area. The results of four standard wipe tests performed at that time indicated very high levels of PCB contamination [i.e., sample .1=106,071 micrograms per 100 square centimeters (ug/100 cm²)] (See Appendix A). Only the PCB 1260 Aroclor was identified in this study.

2.2 CONCRETE REMOVAL

Mr. Hugh Thompson, the present operator of the site, arranged for the removal of the PCB containing transformers and removed most of the visibly oil stained concrete. The contaminated concrete was placed in drums onsite for later disposal (Photograph 4). The removal operation was conducted "dry" (i.e., with a jackhammer). Date is unknown.

2.3 INSPECTION-MDNR

Mr. Henry Rompage Esq. of the USEPA Region VII office stated in a letter dated
June 7, 1989 to Mr. James C. Owen, Esq. that an inspection was conducted of Mr.
Thompson's facility on February 21, 1989 by Mr. Robert Krager of the Missouri
Department of Natural Resources (Appendix B). A soil sample collected from the area
where the concrete pad had been removed showed the presence of 1,200 parts per
million (ppm) PCBs. No other information is available on this inspection.

Table 2-1. Summary of Environmental Sampling and Remediation Work Performed at the Former Carter Carburetor Site

January	1989	A preliminary investigation was performed by Environmental Operations, Inc.
	1989	Heavily contaminated concrete was removed by the present operator.
February	1989	A site inspection and soil sampling was done by the MDNR.
	1989	Additional soil was removed by the present operator.
November	1989	A remediation verification study was conducted by Environmental Operations, Inc.
April	1990	Soil and wipe samples were collected by the USEPA Region VII.
May	1990	A site inspection with concrete sampling was performed by Waste Advisory, Inc.

Source: ESE, 1990.

S-1-24

concre

2.4 REMEDIATION VERIFICATION STUDY

167209 Environmental Operations, Inc. conducted sampling and analysis to determine the effectiveness of the remediation effort (Appendix C). This project, conducted in November 1989, discovered contamination remaining on the surrounding concrete and in the soil underlying the concrete (see Map, Appendix C). The soil levels ranged from 167 to 209 ppm, the levels on the surrounding concrete surfaces ranged from 449 to 5,407 ug/100 cm². Again, only the PCB 1260 Aroclor was identified. The soil contamination may have been due to concrete dust and fragments generated during the removal operation. Several cores of the concrete were taken in the study area during this project. The cores indicated approximately 1/4 inch to 1/2 inch penetration of oil into the concrete. No further testing or analysis was performed on the cores.

2.5 DUST AND SOIL REMOVAL

Mr. Hugh Thompson (operator) removed the concrete dust and some soil in the subject area and placed this material in drums onsite for disposal. Date is unknown.

2.6 EPA STUDY

The United States Environmental Protection Agency Region VII conducted sampling and analysis of the soil and concrete in April and May, 1990. The location of the sampling points is unclear but the report (Appendix D and Photograph 3) indicates that the total PCB concentration in the soils exposed in the concrete removal area range from 17.2 to 18.5 ppm. The wipe samples (exact sampling locations unknown) indicate PCB concentration ranges on the solid surfaces (concrete) from 2.1 to 15,600 ug/cm². Unlike the two early studies conducted by EO which identified only the 1260 Aroclor, the EPA analysis identified a broad range of Aroclors [i.e., 1221 to 1260 (see Appendix D)].

2.7 WASTE ADVISORY, INC. STUDY

In May 1990, Waste Advisory, Inc. along with Brucker and Associates, Ltd. inspected the site and collected three concrete samples from the transformer-circuit breaker area (see Appendix E). The results indicated PCB (1260 Aroclor) concentrations of 225.197, and

2.1

3

3.0 ESE STUDY

Environmental Science & Engineering, Inc. (ESE) was contracted by Waste Advisory, Inc. in September 1990 to:

- 1. Determine the concentration of PCBs on the concrete in and around the transformer-circuit breaker area;
- 2. Determine if the PCB contamination had migrated into the adjacent floor drain; and
- 3. Determine if the dust created during the PCB contaminated concrete removal project has contaminated surfaces in the transformer area.

3.1 SURFACE WIPES

On September 6, 1990 Mr. Scott George of the ESE staff collected 18 wipe samples in and around the transformer-circuit breaker area. The sampling method, as outlined in April 12, 1987 Federal Register 40 CFR Part 761, PCB Spill Cleanup Policy; Final Rule, Section III--Definitions (15) Standard Wipe Test, consisted of wiping a hexane saturated gauze pad over a 100 square centimeter area as outlined by a template (Photographs 1 and 2). Individual templates were used at each sampling site. The hexane wipes were prepared in the laboratory and sealed in glass vials until they were used in the field. Strict decontamination methods were used in the field to prevent cross contamination between samples. One blank sample subjected to field conditions was analyzed for PCBs. One set of sampling replicates (Samples 16 and 17) was collected. Standard and accepted chain-of-custody seals and forms were used. Laboratory quality control is documented in Appendix F, Section 2.

The study area was cleaned of miscellaneous debris and swept clean. The debris and dust was placed in piles for later removal. The individual sampling locations were again swept and gently wiped with a damp cloth to remove any remaining dust. Individual templates were taped to the concrete at each sampling location before sampling started (Photograph 1).

The following is a list of results obtained during the ESE study (see Appendix F and Figure 3-1):

Sample ID	Concentration (ug/100 cm ²)	
Wipe 1	25.3	
Wipe 2	743	
Wipe 3	44.1	.,
Wipe 4	535	
Wipe 5	- 190	•
Wipe 6	1,190	
Wipe 7	97.1	
Wipe 8	2,520	ug 1
Wipe 9	620	<i>v</i>
Wipe 10	· 379	, nocm
Wipe 11	. 191	10
Wipe 12	547	
Wipe 13	32.4	
Wipe 14	74.3	
Wipe 15	338	
Wipe 16	342	
Wipe 17	213	
Dust Wipe	31.0	
Blank	< 1.40	

Note: Only PCB Aroclor 1260 was identified in this study.

As can be seen from this list and Figure 3-1, the concentration of PCBs drop as you move outward from the concrete removal area (former transformer area). It is also apparent that all areas tested exceed the cleanup guideline of 10 ug/100 cm² (see Section 3-4).

3.2 FLOOR DRAIN SAMPLE

A Teflon bailer was used to collect a water sample from the floor drain located adjacent to the west wall (see Figure 3-1 and Photograph 3). The Teflon bailer was thoroughly decontaminated in the laboratory with a soap/water wash, a deionized water rinse, several hexane rinses, and a final deionized water rinse. The bailer was wrapped in aluminum foil until used in the field.

Water is visible in the drain approximately 2 to 3 feet below floor level. Water depth is approximately 6 to 10 inches before the piping turns, either a 90° turn or elbow. The water had a high level of suspended solids and an "oily" appearance. The laboratory results indicated a concentration of 1,620 ppm of PCB Aroclor 1260 in the water. This area will require some form of remediation.

14-10.1

3.3 DUST SAMPLE

A wipe sample of (concrete) dust was collected from a concrete pad approximately 30 feet from the edge of the removal area (see Figure 3-1). The sampling procedure was identical to the methods used for the other wipe samples. The laboratory results indicated 31.0 ug/100 cm² in the sample area. The above results and the presence of white dust (presumably concrete) in the study area indicates extensive cleanup will be required.

3.4 CONCLUSIONS

The ESE study indicates extensive PCB contamination remains in the subject area. This confirms work done earlier by Environmental Operations, Inc.; Missouri Department of Natural Resources; United States Region VII EPA; and Waste Advisory, Inc. Including the present ESE study, a total of six projects have discovered high levels of PCB contamination at the site. Some of this contamination has been removed, but high levels still remain on site.

The ESE study, following well documented procedures and quality control-quality assurance methods, has confirmed the following:

- 1. The concentration of PCBs on the concrete floors in the subject area exceeds the regulatory cleanup levels;
- 2. High levels of PCB contamination have migrated into the floor drain; and
- 3. The dust generated during the concrete removal appears to have spread the contamination further.

The soil cleanup guideline for PCB contamination in restricted access areas is 25 ppm. The cleanup level for indoor surfaces in restricted access areas is 10 ug/100 cm² (standard wipe test) or 100 ug/100 cm² followed by encapsulation (40 CFR Part 761.60; Section IV—Requirements for PCB Spill Cleanup, Subsection C, requirements for cleanup of high-concentration spills and low concentration spills involving 1 pound or more PCBs by weight).

The EPA Region VII has not looked favorably upon the encapsulation option recently due to extensive migration of PCBs through concrete.

No question should remain, that further remediation is required at the subject site. The area should be considered a hazardous waste site and access should be strictly limited.

A human health threat exists in the form of human contact with, and inhalation of, high concentration PCB contaminated dust. The 10-hour time weighted average exposure limit established by NIOSH is 1.0 ug/m³ (NIOSH Guide to Chemical Hazards, U.S. Department of Health and Human Services, 1985). The dust sample collected showed 31.0 ug/100 cm². Polychlorinated biphenyls are listed as a known carcinogen with inhalation, skin absorption, ingestion, skin, and/or eye contact as routes of entry. A strong possibility exists for the further spread of the contamination by human or vehicle traffic. The contamination could also be carried offsite on worker clothing.

It cannot be over emphasized that the area should be sealed and access be allowed only to personnel with appropriate training and protective equipment.

APPENDIX A Environmental Operations, Inc.'s Initial Study

ENVIRONMENTAL ODERATIONS, INC.

HABARDOUS WASTE AND UNDERGROUND TANK MANAGEMENT

905 Park Avenue St. Louis MO 63 1:4 (314) 231-8226

January 26, 1989

Project #2285

Mr. Hugh Thompson P.O. Box 63163 St. Louis, MO 63163

Mr. Thompson: -

This letter is to transmit results of samples collected by Environmental Operations, Inc. and analyzed by Environmetrics, Inc. for Polychlorinated Biphenyls (PCB's) content. The samples were collected by Bill Atkins of Environmental Operations, Inc. on January 16, 1989 at the old Carter Carbaretor facility located at the corner of Grand and St. Louis, Ave.

The purpose of the sampling was to determine if releases had occurred from six high level transformers located on the ground level of the facility and four high level transformers located outside the facility facing Grand Avenue. Also located next to the interior transformers were 16 oil cooled circuit breakers with unknown PCB concentrations. The interior area will be referred to as Bank 2, the exterior as Bank 1.

Samples were collected from areas which visually appeared to have been stailed with oil. The samples were collected by first applying hexane to a piece of of filter paper and thoroughly rubbing this moistened paper over a 100 sq. cm. area of the sample surface (delineated by a template). The filter was immediately placed in a sample bottle which was then tightly capped and labeled.

The results are as follows:

Sample #	Location	Total-micrograms/100 CM2
2265.1	Bank 2 - Southeast	106,071 Fairly high. Direct
2285.2 Interior	Bank 2 - Central West	3,300
2285.3 Transforms to estel	Bank 2 - North, underneath circuit breaker	3,300 all subject to Cleanup.
2285.4	Bank 2 - Central East	1,555)
2235.3 Outside Sampling	Bank 1 - South pad western transformer	<2

A rough sketch of sample locations is attached.

The Environmental Protection Agency (EPA) PCB Spill Clean-up Policy may be found in the Federal Register, Part III, 40 CFR Part 761, issued April 2, 1987. A copy of this regulation is onclosed.

Immediate (48 hours) requirements include (see 40 CFR Part 761 Unit III.C):

- Notification of the EPA regional office and the NRC
- Restrict access to area
- Record and document spill area
- Initiate clean-up

Bank 2 would appear to be a low contact, indoor, non impervious surface, which is addressed in Unit IV, C.3.c. This section states clean up standards of 10micrograms/100cm², or 100micrograms/100cm² and encapsulation.

It should be noted that the samples were collected by selecting a sampling surface which appeared to be worst case. No effort was made to identify contamination boundaries or to estimate volumes of material which would need to be removed to meet the clean up standards. To obtain this information a statistically based sampling scheme should be developed.

Any questions regarding this report may be directed to Bill Atkins or myself at 231-8226.

Sincerely,

Roy P Ningson

Roger R. Hopson President

Enclosures

cc: Skip Colburn

ENVIRONMENTAL OPERATIONS 905 PARK AVENUE ST. LOUIS, MO 63104 **ENVIRONMETRI**

10679 Midwest Industrial St. Louis, MO 6 (314) 427-

JQB #2285


ANALYSIS REPORT

PCBs IN SWABS

sample no.	<u>IDENTIFICATION</u>	TOTAL ug 100 cm²	TYPE
2285-1		106,071	1260
2285-2		3,300	1260
2285-3		660	1260
2285-4		1,555	1260
2285-5		<2	****

JANUARY 24, 1989

WAYNE L. COOPER LABORATORY DIRECTOR



ENVIRONMENTAL OPERATIONS 905 PARK AVENUE ST. LOUIS, MO 63104 ENVIRONMETRIC

10679 Midwest Industrial B: St. Louis, MO 63 (314) 427-0.

JOB #2285

ANALYSIS REPORT

12/

PCBs IN SWABS

SAMPLE NO.	<u>IDENTIFICATION</u>	TOTAL ug 100 cm²	TYPE
2285-1		106,071	1260
2285-2		3,300	1260
2285-3		660	1260
2285-4		1,555	1260
2285-5		<2	

JANUARY 24, 1989

WAYNE L. COOPER LABORATORY DIRECTOR

APPENDIX B USEPA Letter Concerning MDNR Inspection



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION VII 726 MINNESOTA AVENUE KANSAS CITY, KANSAS 66101

June 7, 1989

James C. Owen, Esq. Emerald Point 16141 North Outer Forty Drive, Suite 300 St. Louis, MO 63017

Dear Mr. Owen:

RE: Hubert Thompson
TSCA No. VII-87-T-719

An inspection of Mr. Thompson's facility was conducted by Missouri Department of Natural Resources inspector Robert Krager on February 21, 1989. As part of that inspection he took a soil sample from the area where the concrete pad had been removed. Results of the sample analysis showed the presence of 1200 ppm PCB in said soil sample.

Please advise as to what has been done to address clean up of this area. I would appreciate hearing from you as soon as possible, so that we can conclude this case.

Sincerely,

Henry F. Rompage

Attorney

Office of Regional Counsel

APPENDIX C.

Laboratory Data from the Environmental Operations, Inc.
Remediation Verification Study

ENVIRONMENTAL OPERATIONS 2649 PESTALOZZI STREET ST. LOUIS, MO 63118

ATTENTION: BILL ATKINS

INVOICE: #6708

ENVIRONMETRICS

2345 Millpark Drive Maryland Heights St. Louis County, MO 63043 (314) 427-0550

ANALYSIS REPORT

PCBs IN SOIL

SW-846 8080

	sample 1	IDENTIFICATION	TOTAL DDM	TYPE
•	southernmel.	10 pt eans, 2285.A '	167	1260
ets	northernost	10 pt long. 2285.B"	209	1260
		2285.X	<2	. ==-

NOVEMBER 16, 1989

WAYNE L. COOPER LABORATORY DIRECTOR

ENVIRONMETRICS

2345 Millpark Drive Maryland Height St. Louis County, MO 6304. (314) 427-0550

ENVIRONMENTAL OPERATIONS 2649 PESTALOZZI STREET ST. LOUIS, MO 63118

ATTENTION: BILL ATKINS INVOICE #6708

ANALYSIS REPORT


PCBs IN SWABS

SW-846 8080

SAMPLE £	IDE	NTIFICATION	TOTAL 2	TYPE
2p5	No	2285.C	2,823	1260
30ts	East	2285.D	2,286	1260
2	50	2285.E	449	1260
3	west	2285.F	5,407	1260
feeld be	lens	2285.Y	<2 .	·

NOVEMBER 16, 1989

WAYNE L. COOPER LABORATORY DIRECTOR



APPENDIX D Laboratory Data from EPA Sampling



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION VII 726 MINNESOTA AVENUE KANSAS CITY, KANSAS 66101

May 16, 1990

James C. Owen, Esq. Emerald Point 16141 North Outer Forty Drive Suite 300 St. Louis, MO 63017

Dear Mr. Owen:

Enclosed as you requested, are the sample analysis results for the Thompson property.

Sincerely,

Henry F. Rompage

Attorney

Office of Regional Counsel

Enclosure

ANALYSIS TYPE! PCB DATA

TLEI HUBERT THOMSON B: EPA REGION VII A METHOD: 8701M70 CASE:
AMPLE PREPI ANALYST/ENTRY: SBM REVIEWER: DATE: 04/24/90 SAMPLE PREPI ____

HATRIX: CONTROL BUTTLE UNITS: UB/SHPL

DATA FILE: SBM

SLA74001F

PCB1221 PCB1232 PCB1016 or PCB1242 PCB1248 PCB1254

PCB1260

_.30U .100U .40U MICHOWA Source N .400 .100U

** NOTE: N/A HEANS NOT ANALYZED **

I MEANS ANALYZED BUT INVALID DATA ***

I MEANS ANALYZED BUT INVALID BUT INVALID DATA ***

I MEANS ANALYZED BUT INVALID BUT INVALI ## NOTE! N/A HEANS NOT ANALYZED ##

ANALYSIS TYPE: PCB DATA

TLE: HUBERT THOMSON HATRIX: SUIL UNITE: UG/KG HETHOD: 8701H70 3: EPA REBION VII CASEI BAMPLE PREP:____ ANALYST/ENTRY: SBM REVIEWER: DATE: 04/24/90 DATA FILE: 8BM SLA74002 SLA74003 SLA74004 2000.U 1000.U 3000.U 3000.U 2000.U 2000.U 1000.U 1000.0 3000.U -3000 · U CB1016 or 3000.U 1.000E PCB1242 <u>₩</u> 3000.U ₽ 3000.u 3000.U 3000.U 3000.U TEBIZAGO (3500. (3200. (2100. 3000.1 CB1254 3200. 3500. (2100.

ANALYSIS TYPE: PCB DATA

7				Mi	INC I DAD	1 11	. 65 56	1175					
	LABI	EPA RE	RT THOM	I	T/ENTRY	'i SBM	HATRIX HETHOD REVIEW	1 8701		CASI	rs: U8 E: 04/	/8MPL - 25/90 :	
	• BHNC -	-					DATA F		BH '		•	•	
			. •		8	LA740	05Fdo	SLA740	06	SLA7400	,		
		•		•		/ •3	Ott	1/150.	· .	(1500.U	••		. :
	PCB122 PCB123	1 2	•	•		1 .10	ou	39 50.	2	E00 II	•	• • • • • • • • • • • • • • • • • • • •	
	CB101				•	3 4		Q 200.	n 25.	2000.U 2000.U		آ و و و مهید رمیج رین	
	PCB124 PCB124				(¥),4	ou 🔝 🔪	200.	ָי ע	/2000.U .	· . · .		٠
~	CB125.	<u>:</u>			••	. (. 10		200.		2000.U 5600.			•
,	- () ()	ar later		i. Paganana	nen er		district commen	اعابيا		CHURR	7		•
-	XX TNO	TE1 FN	I/A - HEA	AF TON BN	NALYZED	**	S. C. Berger	TAND!			A IN	1	Ä,
	***	necessia.	•	NS ANALY		INUA	LID DAT	A .***	en er e r en e ner				٠
							""			WE F		13.50	,
*		Manuel		1	JOH GA	1 41 7 7			19				カベ
	30 c (4)	lice real	A Court	الم موران المراكز ولا موران المراكز	A Land Carl								Ų
	19 19 19	101 A	71. 7. 20.				XXX			TANK MANAGE	Handler Hand		T P
	河的连						Town Dall	美加强,					Ś

APPENDIX E Waste Advisory, Inc. Report

June 20, 1990

Mr. Todd Massa, Atty.
Buechner, McCarthy, Leonard
Kaemerer, Owen & Laderman
16141 N. Outer Forty Drive, Ste 300
St. Louis, MO 63017

Dear Mr. Massa:

Jim Owen instructed me to submit this report and proposal on the Hugh Thompson Space Center PCB Clean Up Project to you:

Scott George, presently of Brucker Engineering & Assoc., and I examined the site on the 11th of June, took three samples to establish presence of PCBs in concrete adjacent to the area removed and had them tested. Results with this letter.

We, Waste Advisory, then consulted with Environmental Operations, who has represented the bank (Boatmen's) and has done some sampling and testing of their own. They were kind enough to give us their field sampling sketch and results.

We also spoke with Doug Elders, of the USEPA, who said his agency would like to see Mr. Thompson characterize the PCB contamination thoroughly. He doesn't believe a great many tests would be necessary. He has special concern about the area around the drain and the periphery of the excavated area where the transformers stood.

He also exhibited some concern about general surface contamination from the dust created by the concrete removal that was done earlier by Hugh Thompson.

We discussed encapsulation. He said that really was not an option the EPA could buy in light of its past experience with PCBs migrating through thick sections of concrete.

That same characteristic, especially to be feared in the case of old spills, may make solvent cleaning impractical also. He reports the EPA experience with acid/solvent cleaning to be a mix of success and failure. Failure is usually the result of the high relative permeability of the surface cleaned and age of spill. Deeper contamination means less effective cleaning.

We concluded the EPA would respond favorably to a well-supported, practical site characterizing plan and removal. Whatever is done, according to Mr. Elders, the result must be a clean site.

Accordingly, we asked Scott George to put together a proposal for preliminary site characterization. A copy is enclosed for your examination. Whether Brucker Engineering or Scott's new employer, Environmental Science & Engineering, does the work, the estimated costs will be the same. (My confidence is in the individual, Scott George.)

Once this work is done, we will be in a much better position to identify method and cost of remediation.

We will await your approval before proceeding.

Respectfully submitted,

Wilson M. Powell, CHMM

encl/Brucker proposal Test results Invoice #369

cc/S. George

ENVIRORMETRICS

2345 Millpark Drive Maryland Heights, MO 63043 (314) 427-0550

WASTE ADVISORY, INC. 135 W. ADAMS KIRKWOOD, MO 63122

ATTN: WILSON M. POWELL

INVOICE # 8910

ANALYSIS REPORT

PCBs IN SOLID

SW-846 8080

SAMPLE #	<u>IDENTIFICATION</u>	TOTAL DDM	TYPE
	1	225	1260
	. 2	197	1260
	3	82	1260

JUNE 5, 1990

WAYNE L. COOPER LABORATORY DIRECTOR

APPENDIX F Laboratory Report from the ESE Study



TECHNICAL MEMORANDUM....... .September 24, 1990

Scott George

John Gemoules -FROM:

SUBJECT: Analytical Results for Soil Samples.

Waste Advisory, Inc.

Nineteen (19) wipe, one (1) oil, and one (1) water samples were received in the ESE St. Louis Chemistry Laboratory on September 7, 1990, for PCB analyses. The analyses were performed in accordance with the following methods:

Analysis	Method	Units
PCBs, wipe	GC/ECD	ug-total
PCBs, oil	GC / ECD	mg/kg
PCBs, water	8080	ug/L

A quality control (QC) summary is included in this report. The QC samples analyzed with these samples indicate there were no technical problems with the analyses.

The following are the results for the above mentioned samples.

JFG/pl/REPORT/WAI.RP

11665 Lilburn Park Road

Phone (314) 567-4600

SECTION 1

Analytical Results

ENVIRONMENTAL SCIENCE & ENGINEERING, INC.

09-21-1990

ATUS: FINAL

PAGE# 1

PROJECT NAME:

SCOTT GEORGE PRICT/WASTE ADVISORY, INC.

PROJECT NUMBER: 5902020 0136

FIELD GROUP: HAI

SAMPLE MATRIX:

HIPE

PROJECT MANAGER: JOHN F. GEMOULES

CONCENTRATION

SAMPLE I.D.			CRTR CH-1	CRTR CH-2	CRTR CH-3	CRTR CH-4	CRTR CH-5	CRTR CH-6	CRTR_CH-7	CRTR CH-8
LAB I.D.			HAIMI	HA1*2	EMIAH	HAI#4	HAI*S	HAI#6	WA1*7	B*IAH
COLLECTION DATE			09/06/90	09/06/90	09/06/90	09/06/90	09/06/90	09/06/90	09/06/90	09/06/90
PARAMETER	CAS NUMBER	UNITS								
PCB-1016	12674-11-2	UG	<24.0	<480	<24.0	<24.0	<24.0	<240	(24.0	<240
PCB-1221	11104-28-2	UG	<24.0	<480	<24.0	<24.0	<24.0	<240	<24.0	<240
PCB-1232	11141-16-5	UG	<24.0	<480	<24.0	<24.0	<24.0	<240	<24.0	(240
PCB-1242	53469-21-9	UG	<24.0	<480	<24.0	<24.0	<24.0	<240	<24. 0	<240
PCB-1248	12672-29-6	UG	<24.0	<480	<24.0	<24.0	<24.0 ·	<240	(24.0	<240
PCB-1254	11097-69-1	UG	<24.0	<480	<24.0	<24.0	<24.0	<240	<24.0	<240
PCB-1260	11096-82-5	UG	25.3	743	44.1	535	190	1190	97.1	2520

ENVIRONMENTAL SCIENCE & ENGINEERING, INC. 09-21-1990

3: FINAL

PAGE# 2

PROJECT NAME: SCOTT GEORGE PRJCT/WASTE ADVISORY, INC.

PROJECT NUMBER: 5902020 0136

FIELD GROUP: HAI

SAMPLE MATRIX: WIPE

PROJECT MANAGER: JOHN F. GEMOULES

CONCENTRATION

AMPLE I.D. AB I.D.	-		CRTR CH-9	CRTR CH-10	CRTR CH-11	CRTR CH-12 HAI#12	CRTR CH-13	CRTR CH-14	CRTR CH-15	CRTR CH-16
OLLECTION DATE	·		09/06/90	09/06/90	09/06/90	09/06/90	09/06/90	09/06/90	09/06/90	09/06/90
'ARAMETER	CAS NUMBER	UNITS								
'CB-1016	12674-11-2	UG	<24.0	<240	<24.0	<240	<24.0	<24.0	(240	<240
°CB-1221	11104-28-2	UG .	<24.0	<240	<24.0	<240	<24.0	<24.0	<240	<240
PCB-1232	11141-16-5	UG	<24.0	<240	<24.0	<240	<24.0	(24.0	<240	<240
PCB-1242	53469-21-9	uc	<24.0	<240	<24.0	<240	<24.0	<24.0	<240	<240
PCB-1248	12672-29-6	UG	<24.0	<240	<24.0	<240	<24.0	<24.0	<240	(240
PCB-1254	11097-69-1	UG	<24.0	<240	<24.0	<240	<24.0	<24.0	<240	<240
PCB-1260	11096-82-5	UG	620	379	191	547	32.4	74.3	338	342

ENVIRONMENTAL SCIENCE & ENGINEERING, INC.

09-21-1990

TUS: FINAL

PAGE# 3

PROJECT NAME:

SCOTT GEORGE PRICT/HASTE ADVISORY, INC.

PROJECT NUMBER: 5902020 0136

HIPE

FIELD GROUP: HAT

SAMPLE MATRIX:

PROJECT MANAGER: JOHN F. GEMOULES

CONCENTRATION

SAMPLE 1.D.			CRTR CH-17	DUST HIPE	BL ANK
LAB I.D.			HA1+17	HA * 18	WA1 #20
COLLECTION DATE			09/06/90	09/06/90	09/06/90
PARAMETER	CAS NUMBER	UNITS			
PCB-1016	12674-11-2	UG	<120	<24.0	<2.40
PCB-1221	11104-28-2	UG	<120	<24.0	<2.40
PCB-1232	11141-16-5	UG	<120	<24.0	<2.40
PCB-1242	53469-21-9	UG	<120	<24.0	<2.40
PCB-1248	12672-29-6	UG	<120	<24.0	<2.40
PCB-1254	11097-69-1	UG	<120	<24.0	₹2.40
PCB-1260	11096-82-5	UG	213	31.0	<2.40

ENVIRONMENTAL SCIENCE & ENGINEERING, INC.

09-21-1990

TUS: FINAL

PAGE# 4

PROJECT NAME:

SCOTT GEORGE PRICT/HASTE ADVISORY, INC.

PROJECT NUMBER: 5902020 0136

FIELD GROUP: HAI

SAMPLE MATRIX:

HIPE

PROJECT MANAGER: JOHN F. GEMOULES

CONCENTRATION

SAMPLE I.D.			ASBESTOS
LAB I.D.			HA1+19
COLLECTION DATE			09/06/90
PARAMETER	CAS NUMBER	UNITS	
PCB-1016	12674-11-2	MG/KG-OIL	<1.00
PCB-1221	11104-28-2	MG/KG-OIL	<1.00
PCB-1232	11141-16-5	MG/KG-OIL	<1.00
PCB-1242	53469-22-9	MG/KG-OIL	<1.00
PCB-1248	39500*SECO	MG/KG-OIL	<1.00
PCB-1254	11097-69-1	MG/KG-OIL	<1.00
PCB-1260	11096-82-5	MG/KG-OIL	<1.00

ENVIRONMENTAL SCIENCE & ENGINEERING, INC.

09-21-1990

STATUS: FINAL

PAGE# I

PROJECT NAME:

SCOTT GEORGE PRICT/WASTE ADVISORY, INC.

PROJECT NUMBER: 5902020 0136

FIELD GROUP: HA4-H

SAMPLE MATRIX: WATER PROJECT MANAGER: JOHN F. GENOULES

CONCENTRATION

SAMPLE 1.D. LAB 1.D. COLLECTION DATE			CRTR DRN WAI-WHI 09/06/90
PARAMETER	CAS NUMBER	UNITS	
PCB-1016	12674-11-2	UG/L	<650
PCB-1221	11104-28-2	UG/L	<650
PC8-1232	11141-16-5	UG/L	<650
PCB-1242	53469-22-9	UG/L	<650
PCB-1248	12672-29-6	UG/L	<650
PCB-1254	11097-69-1	UG/L	<650
PCB-1260	11096-82-5	UG/L	1620000

SECTION 2

QC Summary

09/25

Environmental Science and Engineering, Inc.

Page I

Method Blank Sample Summary

NAME	UNITS	STOR*METH	BATCH	SAMPLE	DATE	FOUND
PCB-1016	UG	34671*HIPE	S3868	MB = NONE = 1	09/14/90	0.0
PCB-1221	UG	39488*HIPE		MB*NONE * I		0.0
PCB-1232	UG	39492*WIPE		MB*NONE * 1		0.0
PCB-1242	UG	39496=WIPE		MB*NONE * I		0.0
PCB-1248	UG	39500*HIPE		MB = NONE = I		0.0
PCB-1254	UG	39504*WIPE		MB=NONE = 1		0.0
PCB-1260	UG	39508×W1PE		MB * NONE * I		0.0

Standard Matrix Spike Recovery and Replicate Summary

NAME		UNITS	STOR*METH	BATCH	SAMPLE	DATE	TARGET	FOUND	#RECV	RECV CRI	T .R. P. D.	R.P.D.	CRIT.
PCB-1016		UG	34671*HIPE	23868	SP I * NONE * I	09/14/90	5.00	5.28	106	70-125		25	
PCB-1016	٠	UG			SP2#NONE#1		5.00	5.93	119	70-125	11.6	25	
PCB-1260		UĢ	39508*WIPE		SPI#NONE#1	•	10.0	9.84	98.4	30-130		50	
PCB-1260		UG			SP2#NONE#1		10.0	11.5	115	30-130	15.6	50	

n	q	ı	2	4
v	"	,	•	٠

Environmental Science and Engineering, Inc.

Page 1

Method Blank Sample Summary

NAME	UNITS	STOR*METH	BATCH	SAMPLE	DATE	FOUND
PCB-1016	UG/L	34671*SEC	\$3867	MB*NONE * I	09/14/90	0.0
PCB-1221	UG/L	39488*SEC		MB*NONE * 1		0.0
PCB-1232	UG/L	39492*SEC		MB = NONE = 1		0.0
PCB-1242	UG/L	39496*SEC		MB=NONE = I		0.0
PCB-1248	UG/L	39500*SEC		MB = NONE = 1		0.0
PCB-1254	UG/L	39504*SEC		MB*NONE # I		0.0
PCB-1260	UG/L	39508*SEC		MB*NONE * I		50.4

Standard Matrix Spike Recovery and Replicate Summary

NAME	UNITS	STOR*METH BA	TCH	SAMPLE	DATE	TARGET	FOUND	KRECV	RECV CRIT	R.P.D.	R.P.D. CRIT.
PCB-1016	UG/L	34671*SEC . \$3	1867	SPI*NONE*I	09/14/90	120	136	113	58-130		25
PCB-1016	UG/L			SP2*NONE*1		120	106	88.3	58-130	24.5	25
PCB-1260	UG/L	39508*SEC		SP I *NONE * I		250	297	119	30-130		50
PCB-1260	UG/L			SP2*NONE * I		250	150	59.8	30-130	66.2	50

SECTION 3

Chain of Custody

CHAIN-OF-CUSTODY

ENVIRONMENTAL SCIENCE AND ENGINEERING, INC. PROJECT NUMBER:

09-05-90

FIELD GROUP: WAI-W

PROJECT NAME: SCOTT GEORGE PRJCT/WASTE ADVISORY, INC.

COLLECTION HAZARD COLLECTION SAMPLE I.D. ESE # FRACTIONS (CIRCLE) CODE DATE TIME (Only the first 10 Char. will be used) EC EC WAI-W*1 GarritieriDiriaini NOTE -PLEASE ENTER SAMPLE ID; UP TO 10 ALPHANUMERIC CHARACTERS MAY BE USED.
-CIRCLE FRACTIONS COLLECTED. ENTER DATE, TIME, FIELD DATA (IF REQUIRED), HAZARD CODE AND NOTES -HAZARD CODES: I-IGNITABLE C-CORROSIVE R-REACTIVE T-TOXIC HASTE H-OTHER ACUTE HAZARD; IDENTIFY SPECIFICS IF KNOWN -PLEASE RETURN LOGSHEETS WITH SAMPLES TO ESE RELINOUISHED BY: (NAME/ORGANIZATION/DATE/TIME) RECEIVED BY (NAME/ORGANIZATION/DATE/TIME) OTHER FIELD NOTES FOR FIELD GROUP WAI-W:

LAB NOTES:

Could not fill all 3 bottles

yes you must fill "3" boths for one sample.

とみ

CHAIN-OL JSTODY

ENVIRONMENTAL SCIENCE AND ENGINEERING, INC. PROJECT NUMBER:

09-05-90

FIELD GROUP: WAI

PROJECT NAME: SCOTT GEORGE PRJCT/WASTE ADVISORY, INC.

PROJECT N	umbek:				•	CI/WASTE ADVISORI, INC.
ESE #	FRACTION		AZARD CODE	COLLECTION DATE	COLLECTION TIME	SAMPLE I.D. (Only the first 10 Char. will be used)
WAI*1 P	CB Wie	e (55) (Î)	916190	10:30	Carter SW-11
WAI*2	1			916190	10:40	
WAI*3				916196	10:50	1 1 1 1 1 - 131
WAI * 4				916190	16:00	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
WAI*5	·			916190	11:10	1-151
WAI*6				916190	11 :20	1-161
WAI*7				916190	u :30	1-17
WAI*8				916190	11:40	8
WAI*9				916190	11:50	
WAI*10				916190	. 13:00	1-1/01
WAI*11				91690	12:10	1-111
WAI*12				916190	12:30	1-12
WAI*13		·		916190	12:30	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
WAI*14	1			916 190	12:40	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
WAI*15	Ψ		V	916190	12:50	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
-HAZA	RD CODES: 3	AMPLE ID: UP IS COLLECTED. I-IGNITABLE C-CORROSI LOGSHEETS WIT	VE R-READ	TIVE T-TOXIC WASTE H	CHARACTERS TIELD DATA (I 4-other acute hazard;	MAY BE USED. F REQUIRED), HAZARD CODE AND NOTES IDENTIFY SPECIFICS IF KNOWN
RELIN	QUISHED BY	(NAME/ORGAN	IZATI	ON/DATE/TIME)	REC	EIVED BY (NAME/ORGANIZATION/DATE/TIME)
1 2 6	ed 3Al	ig /ESE	9-7)-9 <i>Q</i>	7.1/2	ESE 9-7-50 0824
OTHER FIEL	D NOTES FOI	R FIELD GROUP	WAI:			
LAB NOTES:			·		. = = = = = = = = = = = =	

----SE INITIAL IF YOU HAVE RECEIVED AND READ THE ENCLOSED INSTRUCTION SHEET

CHAIN-O.

JSTODY

ENVIROND...TAL SCIENCE AND ENGINEERING, INC. PROJECT NUMBER:

09-05-90

FIELD GROUP: WAI

Asbestos Gb.

Blank

PROJECT NAME: SCOTT GEORGE PRJCT/WASTE ADVISORY, INC.

ESE	1	FRACT	rions (CIRCLE	HAZARD) CODE	COLLECTION DATE	ON COLLECT TIME	_	PLE I.D. y the fir	st 10 Cha	ar. will	be used)
WAI * 16	F	CB	Wie	e (55	00	916190	13:00	IC10	urstie	2 m 1C.11	W1-1/61	
WAI*17		4	L	J		916 190	13:10			1 1 1	1=1/2	
NOTE	-PLEASE -CIRCLE -HAZARD -PLEASE	ENTER FRACT CODES RETUR	R SAMPL PIONS C S: I-IGNI RN LOGS	E ID; OLLECT: TABLE C-CO HEETS	UP TO 10 ED. ENTE BROSIVE R-REA WITH SAM	ALPHANUMER R DATE, TIME CTIVE T-TOXIC HAS PLES TO ESE	RIC CHARACT E, FIELD DAT IE H-OTHER ACUTE	ERS MAY BE A (IF REQUI HAZARD: IDENTIFY SP	USED. RED), HAZ	ARD CODE		
						ON/DATE/TIM		RECEIVED		ORGANIZA	•	E/TIME)
1 5	200	<u> 3</u> 8.	Den	Q E	SE	7-7-90	J√	ES La	E. 9-7-	90 08	24	
2				Y								
OTHER	FIELD	NOTES	FOR FI	ELD GR	OUP WAI:						· · · · · · · · · · · · · · · · · · ·	
LAB N	OTES:	Ũ) leas	e a	19:	· · · · · · · · · · · · · · · · · · ·						
W.	1* TA	8:	(55)	7	9	-6-90-	13:20	PCB	Oust	wipe		


9-6-90 - 13:30

WAI * 19


WAI \$20

9-6-90


APPENDIX G Site Photographs from the ESE Study



1. Standard Wipe Test, Sampling Location #2.



2. Study area looking north showing the coacrete removal section and sampling point 12.



3. Study area looking west, bright spot is the floor drain, flags represent EPA sampling locations.



4. PCB contaminated material storage area.